
# ESD product qualification




**Article number:** 0.0.625.33
**Article:** Standard-Fastening Set 8 K ESD

The above-mentioned product's suitability for use in ESD-protected areas (EPA) has been checked in line with the specifications of IEC/DIN EN 61340-5-1:2016 and it meets the relevant requirements.

Typical resistance values at the relevant ambient temperature (measurement voltage: 100 V=)

| Measurements[1] | Standard limit values | Test limit values[2] |
|---|---|---|
| Ambient temperature | 23°C ± 2°C | 23°C ± 2°C |
| Leakage resistance | < $1x10^9$ Ω | < $1x10^9$ Ω |
| Surface resistance | < $1x10^9$ Ω | < $1x10^9$ Ω |
| Volume resistance | < $1x10^9$ Ω | < $1x10^9$ Ω |

[1] Depending on the range of functions and the geometrical dimensions, some measurements may not be relevant.

[2] Due to the local conditions, the relative humidity during all product tests was 10 - 65 percent.

Depending on the application, the entire solution requires additional resistance if the resistance measurement falls below $1x10^4$ Ω.
NB: To ensure safe use in ESD-sensitive environments, measurements must be taken on a regular basis to check that the entire solution in which the product is being used complies with the relevant values (to IEC/DIN EN 61340).

Solingen, 03.02.21

item Industrietechnik GmbH
Friedenstrasse 107-109
42699 Solingen, Germany

Phone +49 212 6580 0
Fax +49 212 6580 310
info@item24.com
item24.com

Quality management to
DIN EN ISO 9001:2015
Solingen, 15 January 2019