



Article number: 0.0.666.77
 Article: Profile X 8 80x40 4NO180 light, natural

The above-mentioned product's suitability for use in ESD-protected areas (EPA) has been checked in line with the specifications of IEC/DIN EN 61340-5-1:2016 and it meets the relevant requirements.

Typical resistance values at the relevant ambient temperature (measurement voltage: 100 V=)

| Measurements ¹ | Standard limit values | Test limit values ² |
|---------------------------|-----------------------|--------------------------------|
| Ambient temperature | 23°C ± 2°C | 23°C ± 2°C |
| Leakage resistance | < 1x10 ⁹ Ω | < 1x10 ⁹ Ω |
| Surface resistance | < 1x10 ⁹ Ω | < 1x10 ⁹ Ω |
| Volume resistance | < 1x10 ⁹ Ω | < 1x10 ⁹ Ω |

¹ Depending on the range of functions and the geometrical dimensions, some measurements may not be relevant.

² Due to the local conditions, the relative humidity during all product tests was 10 - 65 percent.

Depending on the application, the entire solution requires additional resistance if the resistance measurement falls below 1x10⁴ Ω. NB: To ensure safe use in ESD-sensitive environments, measurements must be taken on a regular basis to check that the entire solution in which the product is being used complies with the relevant values (to IEC/DIN EN 61340).

Solingen, 03.02.21